



EPW SERIES

STAGE V
COMPLIANT



Portable generators can be used to power tools and provide emergency backup, as well as tackle site jobs and property improvement works; making it ideal for both work and recreational activities.

The **EPW Series** portable generators provide power where and when you need it.

- ELECTRIC + RECOIL Starting System**
- PORTABILITY**
- LONG RUNNING TIME**
- 13L**
- BATTERY CHARGER**
- DIGITAL DISPLAY**
- OIL BOTTLE FUNNEL PLUGS**



PRODUCT INFO
ALWAYS AVAILABLE ONLINE

Scan the QR to get useful information: product usage and maintenance video tutorials, technical data sheet, direct access to the Service&Parts division and to the usage and maintenance manuals.

- A** Pramac engine for maximum performance on all applications
- B** Automatic Oil guard
- C** Digital display to tracks engine runtime
- D** Fuel gauge to track gasoline levels
- E** Quick starting instruction (QR code and decal)
- F** Schuko sockets and 12V DC
- G** Wheels Kit included



AUTOMATIC VOLTAGE REGULATOR: HOW DOES IT WORK?

Pramac gensets with Automatic Voltage Regulator (AVR) use an electronic control that stabilizes the voltage values, improving the performance and operation of the connected equipment.



EPW 3000

Single Phase Max Power	2900 Watts
Single Phase Rated Power	2700 Watts
Voltage / Hz	230 V / 50 Hz
Running time at 50% load	11.5 Hours
Fuel	Petrol
Displacement	212 cc
Speed (rpm)	3000 rpm
Starting System	Recoil + Electric
Guaranteed sound level (LWA)	96
Noise emission at 7 m	69 dB(A)
Genset dimension LxWxH (mm)	600x456x446
Dry Weight	49 Kg
Socket type Standard EU	2 x Schuko 230V 16A - 12 V DC
Oil guard	✓
Fuel level gauge	✓
Thermal protection	✓
Hour / Volt / Frequency meter	✓
Wheel kit	✓

EPW 5000

Single Phase Max Power	4100 Watts
Single Phase Rated Power	4000 Watts
Voltage / Hz	230 V / 50 Hz
Running time at 50% load	16.3 Hours
Fuel	Petrol
Displacement	274 cc
Speed (rpm)	3000 rpm
Starting System	Recoil + Electric
Guaranteed sound level (LWA)	97
Noise emission at 7 m	70 dB(A)
Genset dimension LxWxH (mm)	600x526x446
Dry Weight	61 Kg
Socket type Standard EU	2 x Schuko 230V 16A - 12 V DC
Oil guard	✓
Fuel level gauge	✓
Thermal protection	✓
Hour / Volt / Frequency meter	✓
Wheel kit	✓



YOUTUBE